

GENERAL INFO AND WARNINGS

- There are no controls and/or useful parts inside the box.
 - **DO NOT OVERVOLT MORE THAN THE NOMINAL 9V DC (CENTER NEGATIVE): THE PEDAL COULD BE DAMAGED AND THE WARRANTY INVALIDATED!**
 - Do not throw water jets directly on the appliance
 - Do not use water steams to clean the appliance
 - Do not use solvents to clean the appliance, especially on the serigraphy
-
- The manufacturer declines all responsibility for any kind of damage to persons, things and/or animals resulting from a wrong use of the appliance
 - The manufacturer reserves the right to make any useful and essential change to the products without compromise the main safety and working features
 - Do not use the appliance barefoot
 - Do not touch the appliance with wet or moist hands or feet
 - Do not allow children or incompetents to use the appliance
 - Do not leave inflammable materials near the appliance
 - Do not pull up the appliance by control knobs
 - Read carefully, compile and deliver the warranty attached to the appliance
 - The appliance repair may be done during the warranty period only by us, in our laboratory, or by authorized staff, in conformity to the national previsions in force
 - In case of damage please contact the shop where you bought the appliance

Please, fill out the warranty form you find on

www.brunetti.it
to validate your warranty

Brunetti Marco & C. S.a.s

Via De' Bonomini, 25/27
41100 MODENA ITALY
Phone: +39 059 243404
Fax: +39 059 216464
e-mail: info@brunetti.it (commercial info)
e-mail: support@brunetti.it (technical info)

Brunetti

Tube amplification

www.brunetti.it
www.brunetti.it/forum

Brunetti

Tube amplification

OWNER'S MANUAL

Mercury
Fluid 2 Distortion

By reading this manual you will deeply know the device you bought and will have the chance to fully experience its potential. Our sets are handmade. This is why you could find some sound and structural differences. This testifies the handmade making of the product

Finest Italian handmade

FEATURES

Mercury2 is the logical MercuryBox evolution. The Mercury2 adds one "solo dedicated" channel to the existing and famous Mercury sound.

The CH2 has own separate Gain and Volume with a Mid eq section added. This design allow to move you "solo" in any musical hue, maintaining the best tonal characteristics. Mercury2 multiplies the versatility of its already well known ancestor, giving you a complete three channels system.

You can move from crunch sounds to hard rock "liquid" distortion which stays defined and never shapeless.

The solos will be very smooth and penetrating, respectful of your instrument timbre.

The feeling playing the Mercury2 is to interact with a real tube amplifier.

These qualities make Mercury2 different, we are sure you will be impressed at first note!

SPECIFICATIONS

- INPUT Impedance = 500 KOhm
- OUTPUT Impedance = 25 KOhm
- Max out level = 600mV
- Weight = 250g / 0,4lbs
- Dimensions = 5.9 x 4.3 x 1.6 inch (150 x 110 x 40 mm)
- Voltage supply MAX 9Vdc
- Max Current absorption = 30mA
- CH2 switching remote jack
- WIMA capacitors, made in Germany
- Metal-film or carbon-film resistors depending on their function
- SH multiwiper potentiometers, aluminium wiper.
- Sealed low power golden relay

CONTROLS

- A - True-bypass switch to engage the effect ON. (Blue LED lighted). OFF mode doesn't affect the original signal
- B - CH2 switch to engage Gain2, Volume2 and Mid control. The Bass and Treble controls keep on work (Red LED lighted)
- C - Input jack from the guitar
- D - CH2 remote jack (let short the tip with ground)
- E - Standard connector for DC 9V (center pin negative)
DO NOT EXCEED 9V SUPPLY TO THE PEDAL ! SERIOUS DAMAGE CAN OCCUR !
- F - Output jact to the amp
- G - VOLUME 1 & 2: Output level controls
- H - BASS: Low frequencies level control
- I - TREBLE: High frequencies control
- J - GAIN 1 & 2: Gain controls
- K - MID: Middle frequencies control. It works on CH2 only

