GENERAL INFO AND WARNINGS

- There are no controls and/or useful parts inside the box. Please open it just to replace the battery.
- TO PROTECT THE BATTERY CONNECTOR WHEN NOT IN USE, IT MUST BE COVERED WITH THE INCLUDED CAP!
- DO NOT OVERVOLT OVER THE NOMINAL 9V DC (CENTER NEGATIVE): THE PEDAL COULD BE DAMAGED AND THE WARRANTY INVALIDATED!
- Do not throw water jets directly on the appliance
- Do not use water steams to clean the appliance
- Do not use solvents to clean the appliance, especially on the serigraphy
- The appliance conformity is proved by CE symbol on the sticker near the 9VDC socket
- The manufacturer declines all responsibility for any kind of damage to persons, things and/or animals resulting from a wrong use of the appliance
- The manufacturer reserves the right to make any useful and essential change to the products without compromise the main safety and working features
- Do not use the appliance barefoot
- Do not touch the appliance with wet or moist hands or feet
- Do not allow children or incompetents to use the appliance
- Do not leave inflammable materials near the appliance
- Do not pull up the appliance by control knobs
- Read carefully, compile and deliver the warranty attached to the appliance
- The appliance repair may be done during the warranty period only by us, in our laboratory, or by authorized staff, in conformity to the national previsions in force
- In case of damage please contact the shop where you bought the appliance

Brunetti Marco & C. S.a.s



Via De' Bonomini, 25/27 41100 MODENA ITALY Phone: +39 059 243404 Fax: +39 059 216464

e-mail: info@brunetti.it (commercial info) e-mail: support@brunetti.it (technical info)

www.brunetti.it www.brunetti.it/forum



OWNER'S MANUAL



By reading this manual you will deeply know the device you bought and will have the chance to fully experience its potential. Our sets are handmade. This is why you could find some sound and structural differences. This testifies the handmade making of the product



FEATURES

Mercury Box is the new Brunetti overdrive/distortion stomp box. A small metallic box holds together the qualities of the well-known CustomWork Mercury's channel 2! It is endowed with "FET" technology to reproduce tubes behavior and dynamics as accurately as possible. Mercury Box is extremely versatile, you can move from clear and defined crunch sounds to hard rock "liquid" distortion which is always clean and never shapeless, very smooth and respectful of your instrument timbre, even at high gain levels. Controls are soft and sentive, but effective at the same time. They indeed interact thoroughly as in a real tube amplifier. Mercury Box arises from careful design and long lasting research of Marco Brunetti, and the outcome is innovative and technologically unique. It is not the upgraded clone of a well-know stomp box! These qualities make Mercury Box different, we are sure you will be impressed at first note!

SPECIFICATIONS

- INPUT Impedance = 500K0hm
- OUTPUT Impedance <= 50K0hm
- Max out level = 600mV
- Weight = about 200g / 0,4lbs
- Dimensions = 100 x 110 x 55 mm
- Current draw = 14mA
- Average 9V (200mA/h) battery life = about 14 hours
- WIMA capacitors, made in Germany
- Metal-film or carbon-film resistors depending on their functions
- SH multiwiper potentiometers, aluminium wiper

CONTROLS

- A True-bypass switch to turn the effect on and off: when Mercury Box is off, it does not alter the original signal
- **B** Output jack to the amp
- C Input jack from the guitar
- D Standard "BOSS" connector for DC 9V (center pin negative).

 DO NOT OVERVOLT THE PEDAL! PROTECT THE BATTERY CONNECTOR

 WITH THE INCLUDED CAP WHEN NOT IN USE!
- **E** VOLUME: effect's otput level control. It is useful to smooth volumes. To increase the signal level output, turn it clockwise
- F BASS: low frequencies level control. To heighten bass presence, turn it clockwise
- **G** EDGE: medium/high frequencies control. To increase medium frequencies and make distortion clearer and more aggressive, turn it clockwise
- H GAIN: gain control. To increase distortion level, turn it clockwise
- I Led that indicates the effect is engaged

