



Tube amplification

USER'S MANUAL

Rocket

Before using, please take few minutes to get familiar with your Amplifier and carefully read the advices, explanations hereby reported. All our units are hand made. For this reason you could find design or sound differences. All this as guarantee that you bought a true hand-made product.

Finest Italian handmade

CONGRATULATION FOR YOUR CHOICE!

Congratulations! You have chosen one of the most innovating Brunetti product.

Rockit is probably the only amplifier for guitars able to match the tube technology with the hexfet modern one. Infact, in a single rack unit, **Rockit** reaches a great result: 60W + 60W stereo or 120W mono in less than 5 Kg!

Its circuitry allows to obtain excellent sound characteristics similar only to the best all-tube amplifiers. The meeting of the hot sound produced by the tubes and the hexfet immediacy creates a great dynamic. Using the "SPECTRAL RESPONSE" knob, you can obtain all kind of sounds from the most classical ones to the most personal ones.

Thanks to its circuitry, **Rockit** allows to use the two channels in bridge (A+B): using the "MONO OUT SPKR" jack, **Rockit** automatically connects in bridge summing the two channels. The "MONO BRIDGE" controls are those of channel "A" with the possibility to add "SPECTRAL RESPONSE" control from channel "B".

Two fans allow the **Rockit** forced cooling, while the conventional one is assured using a heat-sink. For this reason we advise you to ensure the air flux, even if you place your **Rockit** in a rack.

Like all other Brunetti products, **Rockit** has been designed and manufactured following the most accurate handicraft tradition. All the components have been carefully selected and assembled in our factory to offer you the best reliability and quality.

TECHNICAL SPECIFICATIONS

OUTPUT POWER:	Stereo 60W/ch 4/8 Ohm 40W/ch 16 Ohm Mono 120W/ch 16 Ohm do not use speakers with less than 16 Ohm
Input Impedance:	200Kohm
Input Sensitivity:	600mV (max power)
Power Supply:	115/230V - 180VA max
Controlli:	SPECTRAL RESPONSE - POWER LEVEL
Valvole:	2 x 12AU7/ECC82/5814A
Dimensioni:	1U rack - depth 250mm
Peso:	4.5 Kg

EQUIPMENT

- Power cable
- Instruction manual
- Warranty Card

ELECTRIC CONNECTION

- Electric safety and correct work are guarantee when the unit is correctly earthed.
- Ensure that voltage value printed on the rear panel correspond to available current.

CLEANING

Before any kind of cleaning operation, disconnect the appliance from the electric supply.

- Do not throw water jets directly on the appliance.
- Do not use water steams to clean the appliance.
- Do not use solvents to clean the appliance.

Surface Cleaning: system suggested

Satin Aluminium: Soft cloth + product for metal parts

Stainless steel : Paper + product for chrome parts

WARNINGS

- The manufacturer declines all responsibility for any kind of damage to persons, things and/or animals resulting from a wrong use of the appliance.
- The appliance' s conformity is proved by CE symbol on the rear side.
- The manufacturer reserves the right to make any useful and essential change to the products without compromise the main safety and working features.
- Do not use the appliance barefoot.
- Do not touch the appliance with wet or moist hands or feet.
- Do not allow children or incompetents to use the appliance.
- Do not leave inflammable materials near to the appliance.
- Do not pull up the appliance by control knobs.
- Read carefully, compile and deliver the warranty attached to the appliance.
- The appliance' s repair may be done during the warranty period only by us, in our laboratory, or by authorized staff, in conformity to the national previsions in force.
- Control periodically all cables supplied with the appliance, if they result damaged, you have to replace them immediately with another one with the same characteristics.
- In case of damage contact the shop where you bought the appliance.
- The appliance must be earthed in conformity to the national previsions in force.

For any further information and/or support contact us.

Brunetti Marco & C. S.a.s

Via Deí Bonomini, 25/27

I - 41100 MODENA - ITALIA

Phone number : +39 059 / 243404

<http://www.brunetti.it>

e-mail : info@brunetti.it

e-mail : support@brunetti.it

commercial info

technical info